

Vehicle Service Quick Reference Guide

Covering 1998–2012 Honda Vehicles



Accord	1998–2002	2D L4	Civic (Cont.)	2002–2005	Si	Insight	2000–2006	All			
	1998–2002	2D V6		2006–2007	Si		2010–2012	All			
	2003–2005	2D L4		2008–2011	Si		Odyssey	1998	All		
	2006–2007	2D L4		2012	Si			1999–2004	All		
	2008–2012	2D L4		1998–2000	4D			2005–2007	All		
	2003–2005	2D V6		2001–2005	4D			2008–2010	All		
	2006–2007	2D V6		2006–2007	4D		2012	All			
	2008–2012	2D V6		2008–2012	4D		Passport	1998–2002	All		
	1998–2002	4D L4		1998–2000	GX			Not covered	Pilot	2003–2005	All
	1998–2002	4D V6		2001–2005	GX			Not covered		2006–2007	All
	2003–2005	4D L4		2006–2007	GX			Not covered		2008	All
	2006–2007	4D L4		2003–2005	Hybrid			CR-V	2009–2012	All	
	2008–2012	4D L4		2006–2007	Hybrid				1998–2001	All	
	2003–2005	4D V6		2008–2011	Hybrid		2002–2006		All		
	2006–2007	4D V6		2012	Hybrid		2007–2011		All		
	2008–2012	4D V6		2008–2012	Hybrid		2012	All	Prelude	1998–2001	All
	2005	Hybrid		CR-V	1998–2001		All	Ridgeline		2006–2007	All
	2006–2007	Hybrid			2002–2006		All		2008–2012	All	
	Accord	2010–2012		All	CR-V		2007–2011	All	Ridgeline	2006–2007	All
	Crosstour				CR-V		2012	All	S2000	2000–2005	All
Civic	1998–2000	2D	CR-Z	2011	All	S2000	2006–2007	All			
	2001–2005	2D	Element	2003–2006	All		2008–2009	All			
	2006–2007	2D	Element	2007–2011	All		NOTE: For 2013–Later Honda vehicles, refer to the 2013–Later Vehicle Service Quick Reference Guide.				
	2008–2011	2D		Fit	2007–2008	All					
	1998–2000	3D	Fit	2009–2012	All						
	2012	2D/4D									

NOTE: For 2013–Later Honda vehicles, refer to the 2013–Later Vehicle Service Quick Reference Guide.

1998–2002 ACCORD 2D (L4) (7.5K Intervals)

ExpressService™



① Tire Pressure Specifications

All	Remarks
Front: 29 psi Rear: 29 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
Rear Drum: 4–7 clicks Rear Disc: 6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter			
		X	Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
		X	Drain Plug Washer ('98–00 only) (replace at 90K)		M/T	39 N•m (29 lb-ft)
		X	Filler Plug Washer ('98–00 only) (replace at 90K)		M/T	44 N•m (33 lb-ft)
		X	Drain Plug Washer ('98–00 only) (replace at 90K)		A/T	49 N•m (36 lb-ft)
		X	Filler Plug Washer ('98–00 only) (replace at 90K)		A/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.8 qt. (M/T) 5.7 qt. (A/T)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 2.6 qt.	08798-9031 2.0 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Parts Ordering Information

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

1998–2002 ACCORD 2D (V6) (7.5K Intervals)



① Tire Pressure Specifications

LX	EX	Remarks
Front: 30 psi Rear: 30 psi	Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter			
		X	Drain Plug Washer ('98–00 only) (replace at 90K)		A/T	49 N•m (36 lb-ft)
		X	Filler Plug Washer ('98–00 only) (replace at 90K)		A/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
'01–02: 5W-20 08798-9023 '98–00: 5W-30** 08798-9014 5359385 4.6 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.9 qt.	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.1 qt.	N/A	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

** These models can also use 5W-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2003–2005 ACCORD 2D (L4) (10K Intervals)



① Tire Pressure Specifications

EX	LX	Remarks
Front: 32 psi Rear: 30 psi	Front: 30 psi Rear: 29 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
Rear Drum: 4–7 clicks Rear Disc: 6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

10K, 50K, 70K	20K, 40K, 80K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter			

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 4.4 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.4 qt. (M/T) 5.3 qt. (A/T)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.0 qt.	08798-9031 2.0 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2006–2007 ACCORD 2D (L4) (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 30 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
Rear Drum: 4–7 clicks Rear Disc: 6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
			X				Dust & Pollen Filter			
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil 5W-20 08798-9023 4.4 qt. (w/filter) 4.2 qt. (w/o filter)	Brake Fluid DOT 3 08798-9008	Antifreeze/Coolant Type 2* OL999-9011 5.4 qt. (M/T) 5.3 qt. (A/T)	A/T Fluid ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.0 qt.	M/T Fluid 08798-9031 2.0 qt.	P/S Fluid 08206-9002
--	---	--	--	---	--------------------------------

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2008–2012 ACCORD 2D (L4) (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
Rear Disc: 7–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
			X				Dust & Pollen Filter			
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 '08–09: 4.4 qt. (w/filter) 4.2 qt. (w/o filter) '10: 4.2 qt. (w/filter) 4.0 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 Denso: 6.4 qt. (M/T) 6.3 qt. (A/T) TRAD: 6.3 qt. (M/T) 6.2 qt. (A/T)	'08–10: ATF-Z1 08200-9001 or ATF DW-1 08200-9008 '11: ATF DW-1 08200-9008 2.6 qt.	08798-9031 2.0 qt. 5-speed 2.2 qt. 6-speed	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2003–2005 ACCORD 2D (V6) (7.5K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 30 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter			

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 7.1 qt.	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.1 qt.	08798-9031 2.3 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2006–2007 ACCORD 2D (V6) (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 30 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)
				X			Filler Plug Washer		A/T	

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 4.4 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.4 qt. (M/T) 5.3 qt. (A/T)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.0 qt.	08798-9031 2.0 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2008–2012 ACCORD 2D (V6) (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
7–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)
				X			Filler Plug Washer		A/T	

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 '08–'09: 6.9 qt. '10: 6.4 qt.	'08–'10: ATF-Z1 08200-9001 or ATF DW-1 08200-9008 '11: ATF DW-1 08200-9008 3.5 qt.	08798-9031 '08–'10: 2.3 qt. 5-speed '10: 2.2 qt. 6-speed	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

1998–2002 ACCORD 4D (L4) (7.5K Intervals)



① Tire Pressure Specifications

DX	LX/EX/SE	Remarks
Front: 29 psi Rear: 29 psi	Front: 30 psi Rear: 30 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
Rear Drum: 4–7 clicks Rear Disc: 6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter		2 required	
		X	Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
		X	Drain Plug Washer ('98–00 only) (replace at 90K)		M/T	39 N•m (29 lb-ft)
		X	Filler Plug Washer ('98–00 only) (replace at 90K)		M/T	44 N•m (33 lb-ft)
		X	Drain Plug Washer ('98–00 only) (replace at 90K)		A/T	49 N•m (36 lb-ft)
		X	Filler Plug Washer ('98–00 only) (replace at 90K)		A/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
'01–02: 5W-20 08798-9023 '98–00: 5W-30 08798-9014 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.8 qt. (M/T) 5.7 qt. (A/T)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 2.6 qt.	08798-9031 2.6 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

** These models can also use 5W-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

1998–2002 ACCORD 4D (V6) (7.5K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 30 psi Rear: 30 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter		2 required	
		X	Drain Plug Washer ('98–00 only) (replace at 90K)		A/T	49 N•m (36 lb-ft)
		X	Filler Plug Washer ('98–00 only) (replace at 90K)		A/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
'01–02: 5W-20 08798-9023 '98–00: 5W-30 08798-9014 4.6 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.9 qt.	ATF Z1 08200-9001 or ATF DW-1 08200-9008 3.1 qt.	N/A	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

** These models can also use 5W-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2003–2005 ACCORD 4D (L4) (10K Intervals)



① Tire Pressure Specifications

DX/EX	LX	Remarks
Front: 32 psi Rear: 30 psi	Front: 30 psi Rear: 29 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
Rear Drum: 4–7 clicks Rear Disc: 6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

10K, 50K, 70K	20K, 40K, 80K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter			

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 4.4 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.4 qt. (M/T) 5.3 qt. (A/T)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.0 qt.	08798-9031 2.0 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2006–2007 ACCORD 4D (L4) (Maintenance Information)



① Tire Pressure Specifications

VP/EX	LX	Remarks
Front: 32 psi Rear: 30 psi	Front: 30 psi Rear: 29 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
Rear Drum: 4–7 clicks Rear Disc: 6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 4.4 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.4 qt. (M/T) 5.3 qt. (A/T)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.0 qt.	08798-9031 2.0 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2008–2012 ACCORD 4D (L4) (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
08-09 Front/Rear: 32 psi EX, EX-L 2010 Front/Rear: 30 psi LX, LX-P	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
Rear Disc: 7–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 '08–09 4.4 qt. (w/filter) 4.2 qt. (w/o filter) '10: 4.2 qt. (w/filter) 4.0 qt. w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 Denso: 6.4 qt. (M/T) 6.3 qt. (A/T) TRAD: 6.3 qt. (M/T) 6.2 qt. (A/T)	'08–10: ATF-Z1 08200-9001 or ATF DW-1 08200-9008 '11: ATF DW-1 08200-9008 2.6 qt.	08798-9031 2.0 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2003–2005 ACCORD 4D (V6) (7.5K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 30 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter			

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 7.1 qt.	ATF Z1 08200-9001 or ATF DW-1 08200-9008	N/A	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2006–2007 ACCORD 4D (V6) (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 29 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)
							Filler Plug Washer		A/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 4.4 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 7.0 qt. (M/T) 7.1 qt. (A/T)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.2 qt.	08798-9031 2.3 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2008–2011 ACCORD 4D (V6) (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
7–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)
							Filler Plug Washer		A/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 6.9 qt.	'08–10: ATF-Z1 08200-9001 or ATF DW-1 08200-9008 '11: ATF DW-1 08200-9008 3.5 qt.	08798-9031 '08–09 2.3 qt. '10: 2.2 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2005 ACCORD HYBRID (7.5K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 30 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
7-9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter			
		X	Drain Plug Washer (replace at 60K, 90K)		A/T	49 N•m (36 lb-ft)
		X	Filler Plug Washer (replace at 60K, 90K)		A/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 7.1 qt.	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.6 qt.	N/A	N/A

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2006–2007 ACCORD HYBRID (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 29 psi	Spare tire kit, spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
7–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)
				X			Filler Plug Washer		A/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 7.1 qt.	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.2 qt.	N/A	N/A

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2010–2011 ACCORD CROSSTOUR 4D (V6) (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
7–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	6	Description	Special Tools	Remarks	Torque Specs
X	X							Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X							Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X					Air Cleaner Element			
					X			Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
			X					Dust & Pollen Filter			
				X				Drain Plug Washer		A/T	49 N•m (36 lb-ft)
								Filler Plug Washer		A/T	44 N•m (33 lb-ft)
				X				Drain Plug Washer		Transfer Assembly	44 N•m (33 lb-ft)
				X				Filler Plug Washer		Transfer Assembly	44 N•m (33 lb-ft)
							X	Drain Plug Washer		Rear Differential	47 N•m (35 lb-ft)
							X	Filler Plug Washer		Rear Differential	47 N•m (35 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	Transfer Assembly Hypoid Gear Oil, GL-4 or GL-5 SAE 90	Rear Differential Honda Dual Pump Fluid II	P/S Fluid
0W-20 08798-9029 4.4 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 6.9 qt.	'10: ATF-Z1 08200-9001 or ATF DW-1 08200-9008 '11: ATF DW-1 08200-9008 2WD 3.5 qt. 4WD 3.0 qt.	0.4 qt.	08200-9007 1.3 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

1998–2000 CIVIC 2D (7.5K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 30 psi Rear: 29 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
		X	Drain Plug Washer (replace at 90K)		M/T	39 N•m (29 lb-ft)
		X	Filler Plug Washer (replace at 90K)		M/T	44 N•m (33 lb-ft)
		X	Drain Plug Washer (replace at 90K)		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid	CVT Fluid
5W-30** 08798-9014 DX: 3.8 qt. (w/filter) 3.5 qt. (w/o filter) EX/HX: 3.5 qt. (w/filter) 3.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 DX: 3.3 qt. (M/T) 3.2 qt. (A/T) EX/HX: 3.3 qt. (All)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 2.9 qt.	08798-9031 1.9 qt.	08206-9002	08200-9006 4.1 qt.

* Type 2 Antifreeze/Coolant is premixed.

** These models can also use 5W-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2001–2005 CIVIC 2D (10K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 30 psi Rear: 30 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–7 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

10K, 50K, 70K	20K, 40K, 80K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter			
		X	Drain Plug Washer (replace at 60K)		CVT	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid	CVT Fluid
5W-20** 88798-9023 DX/LX: 3.4 qt. (w/filter) 3.2 qt. (w/o filter) HX/EX: 3.7 qt. (w/filter) 3.5 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 4.2 qt. (M/T) 4.1 qt. (A/T, CVT)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 2.9 qt.	08798-9031 1.6 qt.	08206-9002	08200-9006 3.3 qt.

* Type 2 Antifreeze/Coolant is premixed.

** These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2006–2007 CIVIC 2D (Maintenance Information)



① Tire Pressure Specifications

DX	EX/LX	Remarks
Front: 30 psi Rear: 30 psi	Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
8–10 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20** 08798-9023 3.9 qt. (w/filter) 3.7 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.6 qt. (M/T) 5.8 qt. (A/T)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 2.5 qt.	08798-9031 1.5 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

** These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2008–2011 CIVIC 2D (non-Si) (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
8–10 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	08-09 18 N•m (13 lb-ft) 2010 25 N•m (18 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20 08798-9023 3.9 qt. (w/filter) 3.7 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.2 qt. (M/T) 5.5 qt. (A/T)	'08–10: ATF-Z1 08200-9001 or ATF DW-1 08200-9008 '11: ATF DW-1 08200-9008 2.5 qt.	08798-9031 5 speed: 1.5 qt. 6 speed: 1.6 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

1998–2000 CIVIC 3D (7.5K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 30 psi Rear: 29 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
		X	Drain Plug Washer (replace at 90K)		M/T	39 N•m (29 lb-ft)
		X	Filler Plug Washer (replace at 90K)		M/T	44 N•m (33 lb-ft)
		X	Drain Plug Washer (replace at 90K)		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-30** 08798-9014 3.8 qt. (w/filter) 3.5 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 3.3 qt. (M/T) 3.2 qt. (A/T)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 2.9 qt.	08798-9031 1.9 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

** These models can also use 5W-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2002–2005 CIVIC Si (10K Intervals)



① Tire Pressure Specifications

2002–03	2004–05	Remarks
Front: 33 psi Rear: 30 psi	Front: 30 psi Rear: 30 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
7–8 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

10K, 50K, 70K	20K, 40K, 80K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter			

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-30 08798-9014 4.4 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.3 qt.	N/A	08798-9031 1.6 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2006–2007 CIVIC Si (Maintenance Information)



① Tire Pressure Specifications

2006 2D	2007 2D	2007 4D	Remarks
Front: 32 psi Rear: 29 psi	Front: 32 psi Rear: 32 psi	Front: 32 psi Rear: 29 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
8–10 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-30 08798-9014 4.6 qt. (w/filter) 4.4 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.6 qt. 5.8 qt.	N/A	08798-9031 1.6 qt.	N/A

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2008–2011 CIVIC Si (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
All 08-09 Front: 33 psi/Rear: 33 psi 2010 4-dr.Front: 33 psi/Rear 33 psi 2010 2-dr. Front 32 psi/Rear 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
8–10 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	08-09 18 N•m (13 lb-ft) 2010 25 N•m (18 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil 5W-30 08798-9014 4.6 qt. (w/filter) 4.4 qt. (w/o filter)	Brake Fluid DOT 3 08798-9008	Antifreeze/Coolant Type 2* OL999-9011 08-09 5.6 qt. (M/T) 5.8 qt. (A/T) K20Z3 2010 4.7 qt.	A/T Fluid N/A	M/T Fluid 08798-9031 6-spd. 1.6 qt.	P/S Fluid
--	---	---	-------------------------	--	------------------

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2012 CIVIC SI (Maintenance Minder)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	ASpare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
8–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	40 N•m (30 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (32 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Antifreeze/Coolant	A/T Fluid
05W-20 08798-9022 4.4 qt. (w/filter) 4.2 qt. (w/o filter)	Type 2* OL999-9001 1.45 gal.	N/A

M/T Fluid
08798-9031 2.0 qt.

Brake Fluid
DOT 3 08798-9008

⑥ Brake Inspection

Brake Pad Specifications		
Front New 11 mm	Service Limit 1.6 mm	Thickness
Rear New 9 mm	Service Limit 1.6 mm	Thickness

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑦ Additional Parts

See the latest Parts Catalog.

⑧ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

1998–2000 CIVIC 4D (Excluding GX) (7.5 Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 30 psi Rear: 29 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
		X	Drain Plug Washer (replace at 90K)		M/T	39 N•m (29 lb-ft)
		X	Filler Plug Washer (replace at 90K)		M/T	44 N•m (33 lb-ft)
		X	Drain Plug Washer (replace at 90K)		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-30** 08798-9014 DX/LX: 3.8 qt. (w/filter) 3.5 qt. (w/o filter) EX: 3.5 qt. (w/filter) 3.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 DX/LX: 3.3 qt. (M/T) 3.2 qt. (A/T) EX: 3.3 qt. (All)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 2.9 qt.	08798-9031 1.9 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

** These models can also use 5W-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2001–2005 CIVIC 4D (Excluding GX) (10K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 30 psi Rear: 30 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–7 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

10K, 50K, 70K	20K, 40K, 80K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter			

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T	M/T Fluid	P/S Fluid
5W-20** 08798-9023 DX/LX: 3.4 qt. (w/filter) 3.2 qt. (w/o filter) EX: 3.7 qt. (w/filter) 3.5 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 4.2 qt. (M/T) 4.1 qt. (A/T)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 2.9 qt. (A/T)	08798-9031 1.6 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

** These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2006–2007 CIVIC 4D (Maintenance Information)



① Tire Pressure Specifications

DX	EX/LX	Remarks
Front: 30 psi Rear: 30 psi	Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
8–10 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20** 08798-9023 3.9 qt. (w/filter) 3.7 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.6 qt. (M/T) 5.8 qt. (A/T)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 2.5 qt.	08798-9031 1.5 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

** These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2008–2011 CIVIC 4D (Maintenance Information)



① Tire Pressure Specifications

DX	EX/LX	Remarks
Front: 30 psi Rear: 30 psi	Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
8–10 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	08-09 18 N•m (13 lb-ft) 2010 25 N•m (19 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20** 08798-9023 3.9 qt. (w/filter) 3.7 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 '08–'09: 5.6 qt. (M/T)/ 5.8 qt. (A/T) '10: R18A1 5.4 qt. (M/T)/5.6 qt. (A/T)	'08–'10: ATF-Z1 08200-9001 or ATF DW-1 08200-9008 '11: ATF DW-1 08200-9008 2.5 qt.	08798-9031 1.5 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

** These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2012 CIVIC 2D/4D (Maintenance Minder)



① Tire Pressure Specifications

DX/LX	EX/EX-L/HF	Remarks
Front: 30 psi Rear: 30 psi	Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
8–10 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	39 N•m (30 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (32 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Antifreeze/Coolant	A/T Fluid
0W-20 08798-9022 3.9 qt. (w/filter) 3.7 qt. (w/o filter)	Type 2* OL999-9001 1.45 gal.	ATF-DW1 08200-9008 2.5 qt.

M/T Fluid
08798-9031 R18Z1 engine: 1.5 qt. K24Z7 engine: 2.0 qt

Brake Fluid
DOT 3 08798-9008

⑥ Brake Inspection

Brake Pad Specifications		
Front New 10 mm	Service Limit 1.6 mm	Thickness <div style="display: flex; align-items: center; gap: 5px;"> </div> >5 4 ≤3
Rear New 9 mm	Service Limit 1.6 mm	Thickness <div style="display: flex; align-items: center; gap: 5px;"> </div> >5 4 ≤3
Brake Shoe Specifications		
Rear New: 4 mm		Service Limit: 2 mm

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑦ Additional Parts

See the latest Parts Catalog.

⑧ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2003-2005 CIVIC HYBRID (10K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 30 psi Rear: 30 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
8–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

10K, 50K, 70K	20K, 40K, 80K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter		2 required	
		X	Drain Plug Washer		CVT	49 N•m (36 lb-ft)
		X	Filler Bolt Washer		CVT	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	CVT Fluid	M/T Fluid	P/S Fluid
0W-20 08798-9022 3.4 qt. (w/filter) 3.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 4.3 qt. (M/T) 4.2 qt. (CVT)	08200-9006 3.1 qt.	08798-9031 1.6 qt.	N/A

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑧ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2006–2007 CIVIC HYBRID (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
8–10 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		CVT	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	CVT Fluid	M/T Fluid	P/S Fluid
0W-20 08798-9022 3.4 qt. (w/filter) 3.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.0 qt.	08200-9006 3.0 qt.	N/A	N/A

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2008–2011 CIVIC HYBRID (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
8–10 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		CVT	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	CVT Fluid	M/T Fluid	P/S Fluid
0W-20 08798-9022 3.4 qt. (w/filter) 3.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 08-09 4.8 qt. 2010 5.0 qt.	08200-9006 3.0 qt.	N/A	N/A

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2012 CIVIC HYBRID (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
7–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	39 N•m (29 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		CVT	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil 0W-20 08798-9022 3.8 qt. (w/filter) 3.6 qt. (w/o filter)	Antifreeze/Coolant Type 2* OL999-9001 1.37 gal.	CVT Fluid 08200-9006 3.0 qt.	A/T Fluid N/A	Brake Fluid DOT 3 08798-9008
--	---	---	-------------------------	---

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑦ Additional Parts

See the latest Parts Catalog.

⑥ Brake Inspection

Brake Pad Specifications		
Front New 10 mm	Service Limit 1.6 mm	Thickness
Rear New 4.5 mm	Service Limit 2.0 mm	Thickness
Brake Shoe Specifications		
Rear New: 4 mm		Service Limit: 2 mm

⑧ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

1998–2001 CR-V (7.5K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 26 psi Spare: 26 psi Rear: 26 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
2–6 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust and Pollen Filter			
		X	Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
		X	Drain Plug Washer ('98–00 only) (replace at 90K)		M/T	39 N•m (29 lb-ft)
		X	Filler Plug Washer ('98–00 only) (replace at 90K)		M/T	44 N•m (33 lb-ft)
		X	Drain Plug Washer ('98–00 only) (replace at 90K)		A/T	49 N•m (36 lb-ft)
		X	Filler Plug Washer (replace at 90K)		Rear differential	47 N•m (35 lb-ft)
		X	Drain Plug Washer (replace at 90K)		Rear differential	47 N•m (35 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid	Rear Differential Dual Pump Fluid II
5W-30 08798-9014 4.0 qt. (w/filter) 3.7 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 4.2 qt. (M/T) 4.1 qt. (A/T)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.1 qt. (4WD) 2.9 qt. (2WD)	08798-9031 1.8 qt.	08206-9002	08200-9007 1.1 qt.

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2002–2006 CR-V (10K Intervals)



① Tire Pressure Specifications

2002–04	2005–06	Remarks
Front: 26 psi Spare: 26 psi Rear: 26 psi	Front: 29 psi Spare: 29 psi Rear: 29 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
5–9 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

10K, 50K, 70K	20K, 40K, 80K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter			
		X	Drain Plug Washer (replace at 90K)		Rear differential	47 N•m (35 lb-ft)
		X	Filler Bolt Washer (replace at 90K)		Rear differential	47 N•m (35 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid	Rear Differential Dual Pump Fluid II
5W-20** 08798-9023 4.4 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 7.6 qt. (M/T) 5.7 qt. (A/T)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.3 qt. (4WD) '02–04: 3.1 qt. (2WD) '05–06: 3.4 qt. (2WD)	08798-9031 2.0 qt.	08206-9002	08200-9007 '02–04: 1.1 qt. '05–06: 1.3 qt.

* Type 2 Antifreeze/Coolant is premixed.

** These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2007–2011 CR-V (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 30 psi Rear: 30 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–7 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	6	Description	Special Tools	Remarks	Torque Specs
X	X							Drain Bolt Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X							Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X					Air Cleaner Element			
			X					Dust & Pollen Filter			
					X			Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
						X		Drain Plug Washer		Rear differential	47 N•m (35 lb-ft)
						X		Filler Plug Washer		Rear differential	47 N•m (35 lb-ft)
			X					Drain Plug Washer		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil
'07-09: 5W-20 08798-9023** 4.4 qt. (w/filter)/4.2 qt. (w/o filter) '10-11: 0W-20 08798-9022 4.4 qt. (w/filter)/4.2 qt. (w/o filter)

Brake Fluid
DOT 3 08798-9008

Antifreeze/Coolant
Type 2* OL999-9011 08-09 5.3 qt. 2010 6.2 qt.

A/T Fluid
'08-10: ATF-Z1 08200-9001 or ATF DW-1 '11: ATF DW-1 08200-9008 2.6 qt. (4WD) 2.7 qt. (2WD)

Rear Differential Dual Pump Fluid II
08200-9007 1.3 qt.

P/S Fluid
08206-9002

* Type 2 Antifreeze/Coolant is premixed.

**These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2012 CR-V (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
See Driver's Doorjamb Sticker	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
5–6 clicks

③ Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	6	Description	Special Tools	Remarks	Torque Specs
	x							Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	39 N•m (29 lb-ft)
	x							Oil Filter	Light Blue Wrench	¾ turn clockwise	12 N•m (9 lb-ft)
			x					Air Cleaner Element			
			x					Dust & Pollen Filter			
					x			Spark Plugs		Gap: 1.1 mm (0.043 in.)*	18 N•m (13 lb-ft)
				x				Drain Plug Washer		A/T	49 N•m (36 lb-ft)
						x		Drain Plug Washer		Rear differential	47 N•m (35 lb-ft)
							x	Filler Plug Washer		Rear differential	47 N•m (35 lb-ft)

* Do not adjust the gap on iridium-tipped spark plugs

⑤ Oil & Fluid Requirements

Engine Oil	Antifreeze/Coolant	A/T Fluid	Rear Differential Fluid	Brake Fluid	Brake Pad Specifications																		
0W-20 08798-9036 4.2 qt. (w/filter) 4.0 qt. (w/o filter)	Type 2** OL999-9011 1.6 gal.	ATF DW-1 08200-9008 2.3 qt. (2WD) 2.7 qt. (4WD)	Honda Dual Pump Fluid II 08798-9007 1.3 qt.	DOT 3 08798-9008	<table border="1"> <thead> <tr> <th>Front New (2WD)</th> <th>Service Limit</th> <th>Thickness</th> </tr> </thead> <tbody> <tr> <td>11 mm</td> <td>1.6 mm</td> <td>> 5 4 ≤ 3</td> </tr> <tr> <th>Front New (AWD/4WD)</th> <th>Service Limit</th> <th>Thickness</th> </tr> <tr> <td>12.0 mm</td> <td>1.6 mm</td> <td>> 5 4 ≤ 3</td> </tr> <tr> <th>Rear New</th> <th>Service Limit</th> <th>Thickness</th> </tr> <tr> <td>9 mm</td> <td>1.6 mm</td> <td>> 5 4 ≤ 3</td> </tr> </tbody> </table>	Front New (2WD)	Service Limit	Thickness	11 mm	1.6 mm	> 5 4 ≤ 3	Front New (AWD/4WD)	Service Limit	Thickness	12.0 mm	1.6 mm	> 5 4 ≤ 3	Rear New	Service Limit	Thickness	9 mm	1.6 mm	> 5 4 ≤ 3
Front New (2WD)	Service Limit	Thickness																					
11 mm	1.6 mm	> 5 4 ≤ 3																					
Front New (AWD/4WD)	Service Limit	Thickness																					
12.0 mm	1.6 mm	> 5 4 ≤ 3																					
Rear New	Service Limit	Thickness																					
9 mm	1.6 mm	> 5 4 ≤ 3																					

**Type 2 Antifreeze/Coolant is premixed.
NOTE: Always check the oil and fluid levels after filling.

⑦ Additional Parts

See the latest Parts Catalog.

⑧ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2011 CR-Z (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 30 psi Rear: 30 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
5-7 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	39 N•m (29 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.8 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		CVT	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	CVT Fluid	M/T Fluid	P/S Fluid
0W-20 08798-9022 3.8 qt. (w/filter) 3.6 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 4.4L (1.1 gal.).	08200-9006 3.0 qt.	08798-9031 1.5 qt.	N/A

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2003–2006 ELEMENT (10K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 34 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
4–7 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

10K, 50K, 70K	20K, 40K, 80K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust & Pollen Filter			
		X	Drain Plug Washer (replace at 90K)		Rear differential	47 N•m (35 lb-ft)
		X	Filler Bolt Washer (replace at 90K)		Rear differential	47 N•m (35 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid	Rear Differential Dual Pump Fluid II
5W-20** 08798-9023 4.4 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.4 qt. (M/T) 5.3 qt. (A/T)	ATF Z1 08200-9001 or ATF DW-1 08200-9008 3.3 qt. (4WD) 3.4 qt. (2WD)	08798-9031 2.0 qt.	08206-9002	08200-9002 1.1 qt

* Type 2 Antifreeze/Coolant is premixed.

**These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2007-2011 ELEMENT (Maintenance Information)



① Tire Pressure Specifications

EX/LX	SC	Remarks
Front: 33 psi Rear: 35 psi	Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

EX/LX	SC
'07-08: 4-7 clicks '09-10: 12-15 clicks	8-10 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	6	Description	Special Tools	Remarks	Torque Specs
X	X							Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X							Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X					Air Cleaner Element			
			X					Dust & Pollen Filter			
				X				Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
							X	Drain Plug Washer		Rear differential	47 N•m (35 lb-ft)
							X	Filler Plug Washer		Rear differential	47 N•m (35 lb-ft)
				X				Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X				Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X				Drain Plug Washer		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid	Rear Differential Dual Pump Fluid II
5W-20** 08798-9023 4.4 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 5.5 qt. (M/T) 5.4 qt. (A/T)	'07-10: ATF-Z1 08200-9001 or ATF DW-1 08200-9008 '11: ATF DW-1 08200-9008 2.6 qt. (4WD) 2.7 qt. (2WD)	08798-9031 2.0 qt.	08206-9002 0.87 qt.	08200-9007 1.1 qt.

* Type 2 Antifreeze/Coolant is premixed.
**These models can also use OW-20.
NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2007–2008 FIT (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–8 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X	X	X				Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X		X				Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)
				X			Filler Plug Washer		A/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20** 08798-9023 3.8 qt. (w/filter) 3.6 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 4.0 qt. (M/T) 3.9 qt. (A/T)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 2.5 qt.	08798-9031 1.6 qt.	N/A

* Type 2 Antifreeze/Coolant is premixed.

**These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2009-2011 FIT (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
2009 Front/Rear: 32 psi '10-11 except Sport Front/Rear: 32 psi '10-11 Sport Front/Rear: 33 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
5-7 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X	X	X				Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X		X				Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		2009 Gap: 1.1 mm (0.043 in.) 2010 Gap: 1.3 mm (0.051 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X			Filler Plug Washer		M/T	44 N•m (33 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)
				X			Filler Plug Washer (2009 model)		A/T	44 N•m (33 lb-ft)
				X			Filler (thru dipstick opening) (2010 model)		A/T	N/A

⑤ Oil & Fluid Requirements

Engine Oil
5W-20** 08798-9023 3.8 qt. (w/filter)/3.6 qt. (w/o filter)

Brake Fluid
DOT 3 08798-9008

Antifreeze/Coolant
Type 2* OL999-9011 4.6 qt. (M/T) 4.7 qt. (A/T)

A/T Fluid
'09-10:11ATF-Z1 08200-9001 or ATF DW-1 08200-9008 '11: ATF DW-1 08200-9008 2.6 qt.

M/T Fluid
08798-9031 1.6 qt.

P/S Fluid
N/A

* Type 2 Antifreeze/Coolant is premixed.

**These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2000–2006 INSIGHT (7.5K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 38 psi Rear: 35 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
4–8 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust and Pollen Filter			
		X	Drain Plug Washer		CVT	49 N•m (36 lb-ft)
		X	Filler Bolt Washer		CVT	44 N•m (44 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	CVT Fluid	M/T Fluid	P/S Fluid
0W-20 08798-9022 2.6 qt. (w/filter) 2.4 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 '00–03: 2.6 qt. '04–06: 2.4 qt.	08200-9006 3.5 qt.	08798-9031 1.6 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2010-2011 INSIGHT (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 33 psi Rear: 33 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
5-7 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	29 N•m (29 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.8 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		CVT	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	CVT Fluid	M/T Fluid	P/S Fluid
0W-20 08798-9022 3.4 qt. (w/filter) 3.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 4.4L (1.2 gal.).	08200-9006 3.0 qt.	08798-9031 1.5 qt.	N/A

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

1998 ODYSSEY (7.5K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
4–8 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
	X		Drain Plug Washer (replace at 45K, 75K)		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-30 08798-9014 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 6.7 qt.	ATF Z1 08200-9001 or ATF DW-1 08200-9008 2.9 qt.	N/A	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

1999–2004 ODYSSEY (7.5K Intervals)



① Tire Pressure Specifications

1999–2001	2002–04	Remarks
Front: 35 psi Rear: 35 psi	Front: 36 psi Rear: 36 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
Rear Drum: 3–5 clicks Rear Disc: 4–6 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust and Pollen Filter			
	X		Drain Plug Washer (replace at 45K, 75K)		A/T	49 N•m (36 lb-ft)
	X		Filler Plug Washer (replace at 45K, 75K)		A/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
'02–04: 5W-20** 08798-9023 '99–01: 5W-30 08798-9014 4.6 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 7.9 qt. (w/ rear A/C) 5.8 qt. (w/o rear A/C)	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 '02–04: 3.5 qt. '99–01: 3.1 qt.	N/A	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

**These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2005–2007 ODYSSEY (Maintenance Information)



① Tire Pressure Specifications

EX/LX/Touring	EX-L	Remarks
Front: 33 psi Rear: 35 psi	Front: 35 psi Rear: 35 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
4–5 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)
				X			Filler Plug Washer		A/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20** 08798-9023 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 7.4 qt.	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.3 qt.	N/A	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

**These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
127 N•m (94 lb-ft)	Grey Wrench

2008–2010 ODYSSEY (Maintenance Minder)



① Tire Pressure Specifications

EX/LX/Touring	EX-L	Remarks
Front: 33 psi Rear: 35 psi	Front: 35 psi Rear: 35 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
4–5 clicks

③ Battery Specifications

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)
				X			Filler Plug Washer		A/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-20** 08798-9023 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 7.4 qt.	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.3 qt.	N/A	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

**These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
127 N•m (94 lb-ft)	Grey Wrench

2011 ODYSSEY (Maintenance Information)



① Tire Pressure Specifications

EX/LX/EX-L	Touring	Remarks
Front: 33 psi Rear: 33 psi Hi-Speed 35	Front: 35 psi Rear: 35 psi Hi-Speed 36	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
8-10 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	Description	Special Tools	Remarks	Torque Specs
X	X						Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X						Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X				Air Cleaner Element			
			X				Dust & Pollen Filter			
					X		Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
				X			Drain Plug Washer		A/T	49 N•m (36 lb-ft)
				X			Filler Plug Washer		A/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
OW-20** 08798-9022 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 1.93 gal.	ATF-DW-1 08200-9008 or ATF DW-1 08200-9008 3.3 qt.	N/A	08206-9002 1.2 qt.

* Type 2 Antifreeze/Coolant is premixed.

**These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
127 N•m (94 lb-ft)	Grey Wrench

1998–2002 PASSPORT (7.5K Intervals)



① Tire Pressure Specifications

All	Remarks
215/75R15: 29 psi 225/75R16: 29 psi 235/75R15: 29 psi 245/70R16: 26 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–8 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	None	14mm	78 N•m (58 lb-ft)
	X	X	Oil Filter	None		Seat filter, turn 2/3
		X	Air Cleaner Element			

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	P/S Fluid	Front Axle Fluid	Rear Axle Fluid
10W-30 08798-9015 5.0 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 11.7 qt.	Dexron III 9.1 qt.	08206-9002	5113C-3 Mobil 75W-90GL5 1.33 qt.	51015-6 Mobil 80W-90 GL5 1.87 qt.

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
118 N•m (87 lb-ft)	None

2003–2005 PILOT (7.5K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
4–6 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust and Pollen Filter			
	X	X	Drain Plug Washer (replace at 15K, 30K, 60K, 90K)		Rear differential	47 N•m (35 lb-ft)
	X	X	Filler Plug Washer (replace at 15K, 30K, 60K, 90K)		Rear differential	47 N•m (35 lb-ft)
	X		Drain Plug Washer (replace at 45K, 75K)		A/T	49 N•m (36 lb-ft)
	X		Filler Bolt Washer (replace at 45K, 75K)		A/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	VTM-4 Fluid	P/S Fluid
5W-20** 08798-9023 '03–04: 5.1 qt. (w/filter) 4.6 qt. (w/o filter) '05: 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 '03–04: 7.0 qt. '05: 7.6 qt.	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 '03–04: 3.2 qt. '05: 3.9 qt.	08200-9003 2.8 qt.	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

**These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2006–2007 PILOT (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
4–6 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	6	Description	Special Tools	Remarks	Torque Specs
X	X							Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X							Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X					Air Cleaner Element			
			X					Dust & Pollen Filter			
					X			Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
							X	Drain Plug Washer		Rear differential	47 N•m (35 lb-ft)
							X	Filler Plug Washer		Rear differential	47 N•m (35 lb-ft)
				X				Drain Plug Washer		A/T	49 N•m (36 lb-ft)
				X				Filler Bolt Washer		A/T	44 N•m (33 lb-ft)
				X				Drain Plug Washer		A/T transfer assembly	44 N•m (33 lb-ft)
				X				Filler Plug Washer		A/T transfer assembly	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	VTM-4 Fluid	P/S Fluid	Transfer Fluid
5W-20** 08798-9023 4.4 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 7.7 qt.	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.5 qt. (4WD) 4.0 qt. (2WD)	08200-9003 2.8 qt.	08206-9002	GL4 or GL5 0.5 qt.

* Type 2 Antifreeze/Coolant is premixed.

**These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2008 PILOT (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
4–6 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	6	Description	Special Tools	Remarks	Torque Specs
X	X							Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X							Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X					Air Cleaner Element			
			X					Dust & Pollen Filter			
					X			Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
						X		Drain Plug Washer		Rear differential	47 N•m (35 lb-ft)
						X		Filler Plug Washer		Rear differential	47 N•m (35 lb-ft)
				X				Drain Plug Washer		A/T	49 N•m (36 lb-ft)
				X				Filler Bolt Washer		A/T	44 N•m (33 lb-ft)
				X				Drain Plug Washer		A/T transfer assembly	44 N•m (33 lb-ft)
				X				Filler Plug Washer		A/T transfer assembly	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	Diff Fluid	P/S Fluid	Transfer Fluid
5W-20** 08798-9023 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 7.7 qt.	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.5 qt. (4WD) 4.0 qt. (2WD)	08200-9003 2.8 qt.	08206-9002	GL4 or GL5 0.5 qt.

* Type 2 Antifreeze/Coolant is premixed.

**These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2009-2011 PILOT (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
8-10 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	6	Description	Special Tools	Remarks	Torque Specs
X	X							Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X							Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X					Air Cleaner Element			
			X					Dust & Pollen Filter			
					X			Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
							X	Drain Plug Washer		Rear differential	47 N•m (35 lb-ft)
							X	Filler Plug Washer		Rear differential	47 N•m (35 lb-ft)
				X				Drain Plug Washer		A/T	49 N•m (36 lb-ft)
				X				Filler Bolt Washer		A/T	44 N•m (33 lb-ft)
				X				Drain Plug Washer		A/T transfer assembly	44 N•m (33 lb-ft)
				X				Filler Plug Washer		A/T transfer assembly	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	Rear Differential VTM-4 Fluid	P/S Fluid	Transfer Fluid
5W-20** 08798-9023 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 8.0 qt.	'09–10: ATF-Z1 08200-9001 or ATF DW-1 08200-9008 '11: ATF DW-1 08200-9008 '09: 3.0 qt. (4WD)/3.6 qt. (2WD) '10–11: 3.6 qt. (4WD)/3.6 qt.	08200-9003 2.8 qt.	08206-9002 2.8 qt.	GL4 or GL5 0.5 qt.

* Type 2 Antifreeze/Coolant is premixed.

**These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
2009 108 N•m (80 lb-ft)	Red Wrench
2010 127 N•m (94 lb-ft)	Grey Wrench

1998–2001 PRELUDE (7.5K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
6–10 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
		X	Air Cleaner Element			
		X	Dust and Pollen Filter		2 required	
		X	Drain Plug Washer (replace at 90K)		M/T	39 N•m (29 lb-ft)
		X	Filler Plug Washer (replace at 90K)		M/T	44 N•m (33 lb-ft)
		X	Drain Plug Washer (replace at 90K)		A/T	49 N•m (36 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	M/T Fluid	P/S Fluid
5W-30 08798-9014 5.1 qt. (w/filter) 4.8 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 3.5 qt. (M/T) 3.4 qt. (A/T, Type SH)	ATF-Z1 08200-9001 ATF DW-1 08200-9008 2.6 qt.	08798-9031 2.0 qt. 2.2 qt. (Type SH)	08206-9002

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2006–2007 RIDGELINE (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
10–12 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	6	Description	Special Tools	Remarks	Torque Specs
X	X							Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X							Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X					Air Cleaner Element			
			X					Dust & Pollen Filter			
					X			Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
							X	Drain Plug Washer		Rear differential	47 N•m (35 lb-ft)
							X	Filler Plug Washer		Rear differential	47 N•m (35 lb-ft)
				X				Drain Plug Washer		A/T	49 N•m (36 lb-ft)
				X				Filler Bolt Washer		A/T	44 N•m (33 lb-ft)
				X				Drain Plug Washer		A/T transfer assembly	44 N•m (33 lb-ft)
				X				Filler Plug Washer		A/T transfer assembly	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	VTM-4 Fluid	P/S Fluid	Transfer Fluid
5W-20** 08798-9023 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 6.6 qt.	ATF-Z1 08200-9001 or ATF DW-1 08200-9008 3.3 qt.	08200-9003 2.8 qt.	08206-9002	GL4 or GL5 0.5 qt.

* Type 2 Antifreeze/Coolant is premixed.

**These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
127 N•m (94 lb-ft)	Grey Wrench

2008–2011 RIDGELINE (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

② Parking Brake Clicks

All
10–12 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.
--

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	6	Description	Special Tools	Remarks	Torque Specs
X	X							Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X							Oil Filter	Light Blue Wrench	3/4 turn clockwise	12 N•m (8.7 lb-ft)
			X					Air Cleaner Element			
			X					Dust & Pollen Filter			
					X			Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
							X	Drain Plug Washer		Rear differential	47 N•m (35 lb-ft)
							X	Filler Plug Washer		Rear differential	47 N•m (35 lb-ft)
				X				Drain Plug Washer		A/T	49 N•m (36 lb-ft)
				X				Filler Bolt Washer		A/T	44 N•m (33 lb-ft)
				X				Drain Plug Washer		A/T transfer assembly	44 N•m (33 lb-ft)
				X				Filler Plug Washer		A/T transfer assembly	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	A/T Fluid	Rear Differential VTM-4 Fluid	P/S Fluid	Transfer Fluid
5W-20** 08798-9023 4.5 qt. (w/filter) 4.2 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 6.5 qt.	'08–10:ATF-Z1 08200-9001 or ATF DW-1 08200-9008 '11: ATF DW-1 08200-9008 3.3 qt.	08200-9003 2.8 qt.	08206-9002	GL4 or GL5 0.5 qt.

* Type 2 Antifreeze/Coolant is premixed.

**These models can also use OW-20.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
127 N•m (94 lb-ft)	Grey Wrench

2000–2005 S2000 (7.5K Intervals)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

- ◆ DO NOT ROTATE THE TIRES ON THIS VEHICLE.
- ◆ BE CAREFUL WHEN PUTTING A VEHICLE WITH WHEEL STRAKES ON THE SERVICE LIFT.

④ Parts Requirements Quick Reference

7.5K, 22.5K, 37.5K, 52.5K, 67.5K, 82.5K	15K, 45K, 75K	30K, 60K, 90K	Description	Special Tools	Remarks	Torque Specs
X	X	X	Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X	X	Oil Filter	Dark Blue Wrench	7/8 turn clockwise	22 N•m (16 lb-ft)
		X	Air Cleaner Element			
		X	Dust and Pollen Filter			
		X	Drain Plug Washer		Rear differential	45 N•m (33 lb-ft)
		X	Filler Plug Washer		Rear differential	45 N•m (33 lb-ft)
		X	Drain Plug Washer ('00 only) (replace at 90K)		M/T	39 N•m (29 lb-ft)
		X	Filler Plug Washer ('00 only) (replace at 90K)		M/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	M/T Fluid	Differential Oil	P/S Fluid
10W-30 08798-9015 5.1 qt. (w/filter) 4.8 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 6.9 qt.	08798-9031 1.6 qt.	GL5 0.8 qt.	N/A

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

② Parking Brake Clicks

All
9–13 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2006–2007 S2000 (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

- ◆ DO NOT ROTATE THE TIRES ON THIS VEHICLE.
- ◆ BE CAREFUL WHEN PUTTING A VEHICLE WITH WHEEL STRAKES ON THE SERVICE LIFT.

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	6	Description	Special Tools	Remarks	Torque Specs
X	X							Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X							Oil Filter	Dark Blue Wrench	7/8 turn clockwise	22 N•m (16 lb-ft)
			X					Air Cleaner Element			
			X					Dust & Pollen Filter			
					X			Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
							X	Drain Plug Washer		Rear differential	45 N•m (33 lb-ft)
							X	Filler Plug Washer		Rear differential	45 N•m (33 lb-ft)
				X				Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X				Filler Plug Washer		M/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	M/T Fluid	Differential Oil	P/S Fluid
10W-30 08798-9015 5.1 qt. (w/filter) 4.8 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 6.9 qt.	08798-9031 1.6 qt.	GL5 or GL6 0.8 qt.	N/A

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

② Parking Brake Clicks

All
9–13 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench

2008–2009 S2000 (Maintenance Information)



① Tire Pressure Specifications

All	Remarks
Front: 32 psi Rear: 32 psi	Spare tire pressure is 60 psi unless otherwise specified.

◆ DO NOT ROTATE THE TIRES ON THIS VEHICLE.

◆ BE CAREFUL WHEN PUTTING A VEHICLE WITH WHEEL STRAKES ON THE SERVICE LIFT.

④ Parts Requirements Quick Reference

A	B	1	2	3	4	5	6	Description	Special Tools	Remarks	Torque Specs
X	X							Drain Plug Washer (replace at every oil change)	Yellow Wrench	14mm	42 N•m (31 lb-ft)
	X							Oil Filter	Dark Blue Wrench	7/8 turn clockwise	22 N•m (16 lb-ft)
			X					Air Cleaner Element			
			X					Dust & Pollen Filter			
					X			Spark Plugs		Gap: 1.1 mm (0.043 in.)	18 N•m (13 lb-ft)
							X	Drain Plug Washer		Rear differential	45 N•m (33 lb-ft)
							X	Filler Plug Washer		Rear differential	45 N•m (33 lb-ft)
				X				Drain Plug Washer		M/T	39 N•m (29 lb-ft)
				X				Filler Plug Washer		M/T	44 N•m (33 lb-ft)

⑤ Oil & Fluid Requirements

Engine Oil	Brake Fluid	Antifreeze/Coolant	M/T Fluid	Diff Fluid	Differential Oil	P/S Fluid
10W-30 08798-9015 5.1 qt. (w/filter) 4.8 qt. (w/o filter)	DOT 3 08798-9008	Type 2* OL999-9011 6.9 qt.	08798-9031 1.6 qt.	08200-9003 2.8 qt.	GL5 or GL6 0.8 qt.	N/A

* Type 2 Antifreeze/Coolant is premixed.

NOTE: Always check the oil and fluid levels after filling.

⑥ Additional Parts

See the latest Parts Catalog.

② Parking Brake Clicks

All
9–13 clicks

③ Battery Information

For CCA rating, always check the label at the top of the battery. For dealer-installed battery part numbers, see the latest Parts Catalog.

⑦ Wheel Nut Torque

All	Special Tools
108 N•m (80 lb-ft)	Red Wrench