

Vehicle Service Quick Reference Guide

Covering 2013 – Later Honda Vehicles



| Page | Model | Years |
|--------------------|---|-------------|
| 2 | Accord 2D/4D (L4) | 2013 – 2017 |
| 3 | Accord 2D/4D (V6) | 2013 – 2017 |
| 4 | Accord Plug-In | 2014 |
| 5 | Accord Hybrid | 2014 – 2015 |
| 6 | Accord Hybrid | 2017 |
| 7 | Accord (1.5 L) | 2018 |
| 8 | Accord (2.0 L) | 2018 |
| 9 | Accord Hybrid | 2018 |
| 10 | Civic 2D/4D (R18Z1 Engines) | 2013 – 2015 |
| 11 | Civic 2D/4D (K24Z1 Engines) | 2013 – 2015 |
| 12 | Civic Hybrid | 2013 – 2015 |
| 13 | Civic Natural Gas | 2013 – 2015 |
| 14 | Civic (1.5L) | 2016 – 2018 |
| 15 | Civic (2.0L) | 2017 – 2018 |
| 16 | Crosstour (L4) | 2013 – 2015 |
| 17 | Crosstour (V6) | 2013 – 2015 |
| 18 | CR-V | 2013 – 2014 |
| 19 | CR-V | 2015 – 2016 |
| 20 | CR-V | 2017 – 2018 |
| 21 | CR-Z | 2013 – 2016 |
| 22 | Fit | 2013 |
| 23 | Fit | 2015 – 2019 |
| 24 | HR-V | 2016 – 2018 |
| 25 | Insight | 2013 – 2014 |
| 26 | Odyssey | 2013 – 2017 |
| 27 | Odyssey | 2018 – 2019 |
| 28 | Pilot | 2013 – 2015 |
| 29 | Pilot (All Except Touring, Touring Elite) | 2016 – 2018 |
| 30 | Pilot (Touring, Touring Elite Only) | 2016 – 2018 |
| 31 | Ridgeline | 2013 – 2014 |
| 32 | Ridgeline | 2017 – 2018 |

NOTE: For 1998–2012 model Honda vehicles, refer to the 1998-2012 Vehicle Service Quick Reference Guide. (AJA 38835-46571)



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 5-7 Clicks* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Fill Plug (use liquid gasket on threads) | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Check Bolt Washer | | M/T | 12 N•m (9 lb-ft) |
| | | | | x | | | Drain Bolt Washer | | CVT | 49 N•m (36 lb-ft) |
| | | | | x | | | Check Bolt Washer | | CVT | 20 N•m (15 lb-ft) |
| | | | | | x | | Spark Plugs | | 1.0 – 1.1 mm (0.039 - 0.043 in)** | 22 N•m (16 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 4.4 qt. (w/ filter) |
| | | | 4.2 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.6 gal. |
| M/T Fluid | Honda MTF | 08798-9031 | 2.0 qt. |
| CVT Fluid | Honda HCF-2 | 08200-HCF2 | 3.9 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.
NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | | | |
|--------------------------|---------------|-----------|---|-----|
| Front, New (Akebono) | Service Limit | Thickness | | |
| 11 mm | 1.6 mm | > 5 | 4 | ≤ 3 |
| Front, New (Nissin) | Service Limit | Thickness | | |
| 10 mm | 1.6 mm | > 5 | 4 | ≤ 3 |
| Rear, New | Service Limit | Thickness | | |
| 9.5 mm | 1.6 mm | > 5 | 4 | ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 5-7 Clicks* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | M/T | 39 N•m (29 lb-ft) |
| | | | | x | | | Fill Plug (use liquid gasket on threads) | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Check Bolt Washer | | M/T | 12 N•m (9 lb-ft) |
| | | | | x | | | Drain Bolt Washer | | A/T | 49 N•m (36 lb-ft) |
| | | | | | x | | Spark Plugs | | 1.0 – 1.1 mm (0.039 - 0.043 in)** | 22 N•m (16 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 4.5 qt. (w/ filter) |
| | | | 4.2 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.7 gal. |
| M/T Fluid | Honda MTF | 08798-9031 | 2.2 qt. |
| A/T Fluid | ATF DW-1 | 08200-9008 | 3.3 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|---------------|
| Front, New (Akebono) | Service Limit | Thickness |
| 11 mm | 1.6 mm | > 5 4 ≤ 3 |
| Front, New (Nissin) | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 9.5 mm | 1.6 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 7-9 Clicks* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | 8 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | | Dust & Pollen Filter | | | |
| | | | | x | | | | Drain Bolt Washer | | e-CVT | 49 N•m (36 lb-ft) |
| | | | | | x | | | Spark Plugs | | 1.0 – 1.1 mm (0.039 - 0.043 in)** | 22 N•m (16 lb-ft) |
| | | | | | | | x | Air Cleaner Element | | | |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 3.9 qt. (w/ filter) |
| | | | 3.7 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.4 gal. |
| A/T Fluid | ATF DW-1 | 08200-9008 | 2.5 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.
NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|---------------|
| Front, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 9.5 mm | 1.6 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 7-9 Clicks* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | e-CVT | 49 N•m (36 lb-ft) |
| | | | | | x | | Spark Plugs | | 1.0 – 1.1 mm (0.039 - 0.043 in)** | 22 N•m (16 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 3.9 qt. (w/ filter) |
| | | | 3.7 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.4 gal. |
| A/T Fluid | ATF DW-1 | 08200-9008 | 2.5 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.
NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------|
| Front, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 9.5 mm | 1.6 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 7-9 Clicks* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | e-CVT | 49 N•m (36 lb-ft) |
| | | | | x | | | Fill Plug Washer | | e-CVT | 44 N•m (36 lb-ft) |
| | | | | | x | | Spark Plugs | | 1.0 – 1.1 mm (0.039 - 0.043 in)** | 22 N•m (16 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 4.0 qt. (w/ filter) |
| | | | 3.7 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.5 gal. |
| A/T Fluid | ATF DW-1 | 08200-9008 | 2.2 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.
NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------------|
| Front, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 9.5 mm | 1.6 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

3 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|--------------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Fill Plug (use liquid gasket on threads) | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Check Bolt Washer | | M/T | 12 N•m (9 lb-ft) |
| | | | | x | | | Drain Bolt Washer | | CVT | 49 N•m (36 lb-ft) |
| | | | | x | | | Check Bolt Washer | | CVT | 20 N•m (15 lb-ft) |
| | | | | | x | | Spark Plugs | | 0.70 - 0.75 mm (0.0276 - 0.0295 in)* | 22 N•m (16 lb-ft) |

* Do not adjust the gap on iridium-tipped spark plugs.

4 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 3.7 qt. (w/ filter) |
| | | | 3.4 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2** | 0L999-9011 | 1.6 gal. |
| M/T Fluid | Honda MTF | 08798-9031 | 2.0 qt. |
| CVT Fluid | Honda HCF-2 | 08200-HCF2 | 3.8 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

5 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|---------------|
| Front, New (Continental) | Service Limit | Thickness |
| 11 mm | 2.0mm | > 5 4 ≤ 3 |
| Front, New (Nissin) | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 10 mm | 2.0 mm | > 5 4 ≤ 3 |

6 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

3 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|--------------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Fill Plug Washer | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Check Bolt Washer | | M/T | 12 N•m (9 lb-ft) |
| | | | | x | | | Drain Bolt Washer | | A/T | 49 N•m (36 lb-ft) |
| | | | | x | | | Fill Plug Washer | | A/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Check Bolt – Integrated Washer (replace bolt) | | A/T | 20 N•m (15 lb-ft) |
| | | | | x | | | Check Bolt – Separated Washer (replace washer) | | A/T | 20 N•m (15 lb-ft) |
| | | | | | x | | Spark Plugs | | 0.70 - 0.75 mm (0.0276 - 0.0295 in)* | 22 N•m (16 lb-ft) |

* Do not adjust the gap on iridium-tipped spark plugs.

4 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 5.1 qt. (w/ filter) |
| | | | 4.6 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2** | 0L999-9011 | 1.3 gal. |
| M/T Fluid | Honda MTF | 08798-9031 | 2.3 qt. |
| A/T Fluid | ATF Type 2.0 | 08200-9015 | 4.5 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

5 Brake Inspection

| Brake Pad Specifications | | | | |
|--------------------------|---------------|-----------|---|-----|
| Front, New | Service Limit | Thickness | | |
| 11 mm | 2.0mm | > 5 | 4 | ≤ 3 |
| Rear, New | Service Limit | Thickness | | |
| 10 mm | 2.0 mm | > 5 | 4 | ≤ 3 |

6 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 7-9 Clicks* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | e-CVT | 49 N•m (36 lb-ft) |
| | | | | x | | | Fill Plug Washer | | e-CVT | 44 N•m (36 lb-ft) |
| | | | | | x | | Spark Plugs | | 1.0 – 1.1 mm (0.039 - 0.043 in)** | 22 N•m (16 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 4.0 qt. (w/ filter) |
| | | | 3.7 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.5 gal. |
| A/T Fluid | ATF DW-1 | 08200-9008 | 2.3 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.
NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|---------------|
| Front, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 9.5 mm | 1.6 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|---|
| 8-10 Clicks (Rear Disc Brakes)* 7-9 Clicks (Rear Drum Brakes)* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | M/T | 39 N•m (29 lb-ft) |
| | | | | x | | | Fill Plug Washer | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Drain Bolt Washer | | A/T (2013 Models) | 49 N•m (36 lb-ft) |
| | | | | x | | | Drain Bolt Washer | | CVT (2014-15 Models) | 49 N•m (36 lb-ft) |
| | | | | x | | | Check Bolt Washer | | CVT (2014-15 Models) | 44 N•m (32 lb-ft) |
| | | | | | x | | Spark Plugs | | 1.0 - 1.1 mm (0.039 - 0.043 in)** | 18 N•m (13 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Application | Capacity |
|----------------------|---------------|-------------|----------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | ALL | 3.9 qt. (w/ filter) |
| | | | | 3.7 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | ALL | 1.5 gal. |
| M/T Fluid | Honda MTF | 08798-9031 | ALL | 1.5 qt. |
| A/T Fluid | ATF DW-1 | 08200-9008 | 2013 Models | 2.5 qt. |
| CVT Fluid | Honda HCF-2 | 08200-HCF2 | 2014-15 Models | 3.7 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | | |

*** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|---------------------------|---------------|-----------|
| Front, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 9 mm | 1.6 mm | > 5 4 ≤ 3 |
| Brake Shoe Specifications | | |
| Rear, New | Service Limit | |
| 4.0 mm | 2.0mm | |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 8-9 Clicks* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | M/T | 39 N•m (29 lb-ft) |
| | | | | x | | | Fill Plug Washer | | M/T | 44 N•m (32 lb-ft) |
| | | | | | x | | Spark Plugs | | 1.0 - 1.1 mm (0.039 - 0.043 in)** | 18 N•m (13 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 4.4 qt. (w/ filter) |
| | | | 4.2 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.5 gal. |
| M/T Fluid | Honda MTF | 08798-9031 | 1.5 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------|
| Front, New | Service Limit | Thickness |
| 11 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 9 mm | 1.6 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 7-9 Clicks* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | CVT | 49 N•m (36 lb-ft) |
| | | | | | x | | Spark Plugs | | 1.0 - 1.1 mm (0.039 - 0.043 in)** | 27 N•m (20 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 3.6 qt. (w/ filter) |
| | | | 3.4 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.4 gal. |
| CVT Fluid | Honda CVTF | 08200-9006 | 3.0 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.
NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|---------------|
| Front, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |

| Brake Shoe Specifications | |
|---------------------------|---------------|
| Rear, New | Service Limit |
| 4.5 mm | 2.0 mm |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 7-9 Clicks* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | x | | | | Fuel Filter A | | | |
| | | | | x | | | Drain Bolt Washer | | A/T | 49 N•m (36 lb-ft) |
| | | | | | x | | Spark Plugs | | 0.7 - 0.8 mm (0.028 - 0.031 in)** | 18 N•m (13 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 3.9 qt. (w/ filter) |
| | | | 3.7 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.5 gal. |
| A/T | ATF DW-1 | 08200-9008 | 2.5 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.
NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|--|
| Front, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |

| Brake Shoe Specifications | |
|---------------------------|---------------|
| Rear, New | Service Limit |
| 4.5 mm | 2.0 mm |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

3 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|--------------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Fill Plug Washer | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Drain Bolt Washer | | CVT | 49 N•m (36 lb-ft) |
| | | | | x | | | Check Bolt Washer | | CVT | 20 N•m (15 lb-ft) |
| | | | | | x | | Spark Plugs (Si only) | | 0.70 - 0.75 mm (0.0276 - 0.0295 in)* | 22 N•m (16 lb-ft) |
| | | | | | x | | Spark Plugs | | 0.70 - 0.80 mm (0.028 - 0.031 in)* | 22 N•m (16 lb-ft) |

* Do not adjust the gap on iridium-tipped spark plugs.

4 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 3.7 qt. (w/ filter) |
| | | | 3.4 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2** | 0L999-9011 | 1.4 gal. |
| M/T Fluid | Honda MTF | 08798-9031 | 2.0 qt. |
| CVT Fluid | Honda HCF-2 | 08200-HCF2 | 3.9 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

5 Brake Inspection

| Brake Pad Specifications | | | | |
|--------------------------|---------------|-----------|---|-----|
| Front, New | Service Limit | Thickness | | |
| 11 mm | 1.6mm | > 5 | 4 | ≤ 3 |
| Rear, New | Service Limit | Thickness | | |
| 10 mm | 2.0 mm | > 5 | 4 | ≤ 3 |

6 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

3 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|------------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts (Type R) | Gray Wrench | | 127 N•m (94 lb-ft) |
| | | x | | | | | Wheel Nuts (LX) | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Fill Plug Washer | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Check Bolt Washer | | M/T | 12 N•m (9 lb-ft) |
| | | | | x | | | Drain Bolt Washer | | CVT | 49 N•m (36 lb-ft) |
| | | | | x | | | Check Bolt Washer | | CVT | 44 N•m (32 lb-ft) |
| | | | | | x | | Spark Plugs (Type R) | | 0.70 - 0.80 mm (0.028 – 0.031 in)* | 22 N•m (16 lb-ft) |
| | | | | | x | | Spark Plugs (LX) | | 1.0 – 1.1 mm (0.039 – 0.043 in)* | 22 N•m (16 lb-ft) |

* Do not adjust the gap on iridium-tipped spark plugs.

4 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Application | Capacity |
|----------------------|---------------|-------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | Type R | 5.7 qt. (w/ filter) |
| | | | | 5.3 qt. (w/o filter) |
| | | | LX | 4.4 qt. (w/ filter) |
| | | | | 4.2 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2** | 0L999-9011 | Type R | 1.2 gal. |
| | | | LX | 1.4 gal. |
| M/T Fluid | Honda MTF | 08798-9031 | Type R | 2.3 qt. |
| CVT Fluid | Honda HCF-2 | 08200-HCF2 | LX | 3.7 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | | |

** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

5 Brake Inspection

| Brake Pad Specifications | | | | |
|--------------------------|---------------|-----------|---|-----|
| Front, New (Type R) | Service Limit | Thickness | | |
| 10 mm | 2.0 mm | > 5 | 4 | ≤ 3 |
| Front, New (LX) | Service Limit | Thickness | | |
| 11 mm | 1.6 mm | > 5 | 4 | ≤ 3 |
| Rear, New | Service Limit | Thickness | | |
| 9.5 mm | 2.0 mm | > 5 | 4 | ≤ 3 |

6 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 7-9 Clicks* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | 6 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | | Air Cleaner Element | | | |
| | | | x | | | | | Dust & Pollen Filter | | | |
| | | | | x | | | | Drain Bolt Washer | | A/T | 49 N•m (36 lb-ft) |
| | | | | | x | | | Spark Plugs | | 1.0 – 1.1 mm (0.039 – 0.043 in)** | 18 N•m (13 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 4.2 qt. (w/ filter) |
| | | | 4.0 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.7 gal. |
| A/T Fluid | ATF DW-1 | 08200-9008 | 2.6 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------|
| Front, New | Service Limit | Thickness |
| 12 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 9 mm | 1.6 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 7-9 Clicks* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | 6 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | | Air Cleaner Element | | | |
| | | | x | | | | | Dust & Pollen Filter | | | |
| | | | | x | | | | Drain Bolt Washer | | A/T | 49 N•m (36 lb-ft) |
| | | | | x | | | | Fill Plug Washer | | A/T | 44 N•m (32 lb-ft) |
| | | | | x | | | | Drain Bolt Washer | | Transfer Assembly (4WD) | 44 N•m (32 lb-ft) |
| | | | | x | | | | Fill Plug Washer | | Transfer Assembly (4WD) | 44 N•m (32 lb-ft) |
| | | | | | x | | | Spark Plugs | | 1.0 – 1.1 mm (0.039 – 0.043 in)** | 22 N•m (16 lb-ft) |
| | | | | | | x | | Drain Bolt Washer | | Rear Differential (4WD) | 47 N•m (35 lb-ft) |
| | | | | | | | x | Fill Plug Washer | | Rear Differential (4WD) | 47 N•m (35 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|-------------------------|--------------------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 4.5 qt. (w/ filter) |
| | | | 4.2 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 2.0 gal. |
| A/T Fluid | ATF DW-1 | 08200-9008 | 3.3 qt. |
| Transfer Assembly Fluid | HGO-1 | 08200-9014 | 0.4 qt. |
| Rear Differential Fluid | Honda Dual Pump Fluid II | 08200-9007 | 1.3 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.
NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------|
| Front, New | Service Limit | Thickness |
| 12 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 9 mm | 1.6 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 5-6 Clicks* |

* When lever is pulled with 294 N (30.0 kgf, 66.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | 6 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | | Air Cleaner Element | | | |
| | | | x | | | | | Dust & Pollen Filter | | | |
| | | | | x | | | | Drain Bolt Washer | | A/T | 49 N•m (36 lb-ft) |
| | | | | | x | | | Spark Plugs | | 1.0 – 1.1 mm (0.039 – 0.043 in)** | 22 N•m (16 lb-ft) |
| | | | | | | x | | Drain Bolt Washer | | Rear Differential (AWD) | 47 N•m (35 lb-ft) |
| | | | | | | | x | Fill Plug Washer | | Rear Differential (AWD) | 47 N•m (35 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Application | Capacity |
|-------------------------|--------------------------|-------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | ALL | 4.2 qt. (w/ filter) |
| | | | | 4.0 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | ALL | 1.7 gal. |
| A/T Fluid | ATF DW-1 | 08200-9008 | AWD | 2.7 qt. |
| | | | 2WD | 2.3 qt. |
| Rear Differential Fluid | Honda Dual Pump Fluid II | 08200-9007 | ALL | 1.3 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | ALL | |

*** Type 2 Antifreeze / Coolant is premixed.
NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------|
| Front, New (AWD) | Service Limit | Thickness |
| 12 mm | 1.6 mm | > 5 4 ≤ 3 |
| Front, New (2WD) | Service Limit | Thickness |
| 11 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 9.5 mm | 2.0 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 5-6 Clicks* |

* When lever is pulled with 294 N (30.0 kgf, 66.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | 6 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | | Air Cleaner Element | | | |
| | | | x | | | | | Dust & Pollen Filter | | | |
| | | | | x | | | | Drain Bolt Washer | | CVT | 49 N•m (36 lb-ft) |
| | | | | x | | | | Check Bolt Washer | | CVT | 20 N•m (15 lb-ft) |
| | | | | | x | | | Spark Plugs | | 1.0 – 1.1 mm (0.039 – 0.043 in)** | 22 N•m (16 lb-ft) |
| | | | | | | x | | Drain Bolt Washer | | Rear Differential (AWD) | 47 N•m (35 lb-ft) |
| | | | | | | | x | Fill Plug Washer | | Rear Differential (AWD) | 47 N•m (35 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Application | Capacity |
|-------------------------|--------------------------|-------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | ALL | 4.6 qt. (w/ filter) |
| | | | | 4.4 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | ALL | 1.7 gal. |
| CVT Fluid | Honda HCF-2 | 08200-HCF2 | AWD | 4.5 qt. |
| | | | 2WD | 3.9 qt. |
| Rear Differential Fluid | Honda Dual Pump Fluid II | 08200-9007 | ALL | 1.3 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | ALL | |

*** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|---------------|
| Front, New (AWD) | Service Limit | Thickness |
| 12 mm | 1.6 mm | > 5 4 ≤ 3 |
| Front, New (2WD) | Service Limit | Thickness |
| 11 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 9 mm | 1.6 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

3 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | 6 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|---|-------------------|--------------------------------------|--------------------|
| x | x | | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | | Air Cleaner Element | | | |
| | | | x | | | | | Dust & Pollen Filter | | | |
| | | | | x | | | | Drain Bolt Washer | | CVT | 49 N•m (36 lb-ft) |
| | | | | x | | | | Check Bolt Washer | | CVT | 20 N•m (15 lb-ft) |
| | | | | | x | | | Spark Plugs (1.5 L) | | 0.70 - 0.75 mm (0.0276 - 0.0295 in)* | 22 N•m (16 lb-ft) |
| | | | | | x | | | Spark Plugs (2.4 L) | | 1.0 - 1.1 mm (0.039 - 0.043 in)* | 22 N•m (16 lb-ft) |
| | | | | | | x | | Drain Bolt Washer | | Rear Differential (AWD) | 47 N•m (35 lb-ft) |
| | | | | | | | x | Fill Plug Washer | | Rear Differential (AWD) | 47 N•m (35 lb-ft) |

* Do not adjust the gap on iridium-tipped spark plugs.

4 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Application | Capacity |
|-------------------------|--------------------------|-------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 1.5 L | 3.5 qt. (w/ filter) |
| | | | | 3.2 qt. (w/o filter) |
| | | | 2.4 L | 4.4 qt. (w/ filter) |
| | | | | 4.2 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2** | 0L999-9011 | ALL | 1.7 gal. |
| CVT Fluid | Honda HCF-2 | 08200-HCF2 | AWD | 4.3 qt. |
| | | | 2WD | 3.7 qt. |
| Rear Differential Fluid | Honda Dual Pump Fluid II | 08200-9007 | ALL | 1.3 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | ALL | |

** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

5 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------|
| Front, New | Service Limit | Thickness |
| 11 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |

6 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------------------|
| 5-7 Clicks* (2013-2015) |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|---------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | M/T | 39 N•m (29 lb-ft) |
| | | | | x | | | Fill Plug Washer | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Drain Bolt Washer | | CVT | 49 N•m (36 lb-ft) |
| | | | | | x | | Spark Plugs | | 1.2-1.3 mm (0.047 - 0.051 in)** | 27 N•m (20 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 3.8 qt. (w/ filter) |
| | | | 3.6 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.2 gal. |
| M/T Fluid | Honda MTF | 08798-9031 | 1.5 qt. |
| CVT Fluid | Honda CVTF | 08200-9006 | 3.0 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.
NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | | | |
|--------------------------|---------------|-----------|---|-----|
| Front, New | Service Limit | Thickness | | |
| 10 mm (2013-2015) | 1.6 mm | > 5 | 4 | ≤ 3 |
| 11 mm (2016) | | | | |
| Rear, New | Service Limit | Thickness | | |
| 9 mm (2013-2015) | 1.6 mm | > 5 | 4 | ≤ 3 |
| 10 mm (2016) | | | | |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 5-7 Clicks* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|----------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | M/T | 39 N•m (29 lb-ft) |
| | | | | x | | | Fill Plug Washer | | M/T | 49 N•m (36 lb-ft) |
| | | | | x | | | Drain Bolt Washer | | A/T | 49 N•m (36 lb-ft) |
| | | | | | x | | Spark Plugs | | 1.2 – 1.3mm (0.047 - 0.051 in)** | 18 N•m (13 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 3.8 qt. (w/ filter) |
| | | | 3.6 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.2 gal |
| M/T Fluid | Honda MTF | 08798-9031 | 1.6 qt. |
| A/T Fluid | ATF DW-1 | 08200-9008 | 2.6 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.
NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------|
| Front, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |

| Brake Shoe Specifications | |
|---------------------------|---------------|
| Rear, New | Service Limit |
| 4.5 mm | 1.0 mm |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|--------------|
| 8-10 Clicks* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | M/T | 39 N•m (29 lb-ft) |
| | | | | x | | | Fill Plug Washer | | M/T | 49 N•m (36 lb-ft) |
| | | | | x | | | Drain Bolt Washer | | CVT | 44 N•m (32 lb-ft) |
| | | | | x | | | Fill Plug Washer | | CVT | 44 N•m (32 lb-ft) |
| | | | | | x | | Spark Plugs | | 1.0 – 1.1 mm (0.039 - 0.043 in)** | 18 N•m (13 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|---------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 3.5 qt. (w/ filter) |
| | | | 3.3 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.0 gal. |
| M/T Fluid | Honda MTF | 08798-9031 | 1.6 qt. |
| CVT Fluid | Honda HCF-2 | 08200-HCF2 | 3.6 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------------|
| Front, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |

| Brake Shoe Specifications | |
|---------------------------|---------------|
| Rear, New | Service Limit |
| 4.5 mm | 1.0 mm |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

3 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | 6 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|---|-------------------|----------------------------------|--------------------|
| x | x | | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | | Air Cleaner Element | | | |
| | | | x | | | | | Dust & Pollen Filter | | | |
| | | | | x | | | | Drain Bolt Washer | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | | Fill Bolt Washer | | M/T | 44 N•m (32 lb-ft) |
| | | | | x | | | | Drain Bolt Washer | | CVT | 49 N•m (36 lb-ft) |
| | | | | x | | | | Check Bolt Washer | | CVT | 44 N•m (32 lb-ft) |
| | | | | | x | | | Spark Plugs | | 1.0 – 1.1 mm (0.039 – 0.043 in)* | 22 N•m (16 lb-ft) |
| | | | | | | x | | Drain Bolt Washer | | Rear Differential (AWD) | 47 N•m (35 lb-ft) |
| | | | | | | | x | Fill Plug Washer | | Rear Differential (AWD) | 47 N•m (35 lb-ft) |

* Do not adjust the gap on iridium-tipped spark plugs.

4 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Application | Capacity |
|-------------------------|--------------------------|-------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | ALL | 3.7 qt. (w/ filter) |
| | | | | 3.5 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2** | 0L999-9011 | ALL | 1.4 gal. |
| M/T Fluid | Honda MTF | 08798-9031 | M/T | 2.0 qt. |
| CVT Fluid | Honda HCF-2 | 08200-HCF2 | AWD | 4.2 qt. |
| | | | 2WD | 3.7 qt. |
| Rear Differential Fluid | Honda Dual Pump Fluid II | 08200-9007 | ALL | 1.3 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | ALL | |

** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

5 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|---------------|
| Front, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |

6 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|-------------|
| 6-8 Clicks* |

* When lever is pulled with 196 N (20.0 kgf, 44.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Red Wrench | | 108 N•m (80 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | CVT | 49 N•m (36 lb-ft) |
| | | | | | x | | Spark Plugs | | 1.0 – 1.1 mm (0.039 - 0.043 in)** | 27 N•m (20 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|----------------------|-----------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 3.4 qt. (w/ filter) |
| | | | 3.2 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.2 gal. |
| CVT Fluid | Honda CVT Fluid | 08200-9006 | 3.0 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.
NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------|
| Front, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |

| Brake Shoe Specifications | |
|---------------------------|---------------|
| Rear, New | Service Limit |
| 4.5 mm | 1.0 mm |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|--------------|
| 8-10 Clicks* |

* When lever is pulled with 294 N (30.0 kgf, 66.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Gray Wrench | | 127 N•m (94 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | A/T | 49 N•m (36 lb-ft) |
| | | | | x | | | Fill Plug Washer | | A/T | 44 N•m (32 lb-ft) |
| | | | | | x | | Spark Plugs | | 1.0 - 1.1 mm (0.039 - 0.043 in)** | 22 N•m (16 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Application | Capacity |
|----------------------|----------------------|-------------|------------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | ALL | 4.5 qt. (w/ filter) |
| | | | | 4.2 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | ALL | 2.0 gal. |
| A/T Fluid | ATF DW-1 | 08200-9008 | 2013 non-Touring | 3.1 qt. |
| | | | 2013 Touring | 3.6 qt. |
| | | | 2014-2017 ALL | |
| Brake Fluid | DOT 3 | 08798-9008 | ALL | |
| Power Steering Fluid | Power Steering Fluid | 08206-9002 | ALL | |

*** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|---------------|
| Front, New | Service Limit | Thickness |
| 12 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|--------------|
| 8-10 Clicks* |

* When lever is pulled with 294 N (30.0 kgf, 66.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | Wheel Nuts | Gray Wrench | | 127 N•m (94 lb-ft) |
| | | | x | | | | Air Cleaner Element | | | |
| | | | x | | | | Dust & Pollen Filter | | | |
| | | | | x | | | Drain Bolt Washer | | 9-speed A/T | 35 N•m (26 lb-ft) |
| | | | | x | | | Fill Plug Washer | | 9-speed A/T | 35 N•m (26 lb-ft) |
| | | | | x | | | Drain Bolt Washer | | 10-speed A/T | 49 N•m (36 lb-ft) |
| | | | | x | | | Fill Plug Washer | | 10-speed A/T | 44 N•m (32 lb-ft) |
| | | | | x | | | Check Bolt – Integrated Washer (replace bolt) | | 10-speed A/T | 20 N•m (15 lb-ft) |
| | | | | x | | | Check Bolt – Separated Washer (replace washer) | | 10-speed A/T | 20 N•m (15 lb-ft) |
| | | | | | x | | Spark Plugs | | 1.0 - 1.1 mm (0.039 - 0.043 in)** | 22 N•m (16 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Application | Capacity |
|----------------------|----------------------|-------------|-------------|--------------------------------------|
| Engine Oil | 0W-20 | 08798-9036 | ALL | 5.7 qt. (w/ filter) |
| | | | | 5.4 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | ALL | 1.7 gal. |
| A/T Fluid | ATF Type 3.1**** | 08200-9017 | 9-speed | 3.5 qt. |
| | ATF Type 2.0**** | 08200-9015 | 10-speed | 4.8 qt. (Type A) 4.5 qt. (Type B) |
| Brake Fluid | DOT 3 | 08798-9008 | ALL | |
| Power Steering Fluid | Power Steering Fluid | 08206-9002 | ALL | |

**** Type 2 Antifreeze / Coolant is premixed.

***** Do not check the ATF fluid level unless you are replacing it.

NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------|
| Front, New | Service Limit | Thickness |
| 11 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|--------------|
| 8-10 Clicks* |

* When lever is pulled with 294 N (30.0 kgf, 66.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | 6 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | | Wheel Nuts | Gray Wrench | | 127 N•m (94 lb-ft) |
| | | | x | | | | | Air Cleaner Element | | | |
| | | | x | | | | | Dust & Pollen Filter | | | |
| | | | | x | | | | Drain Bolt Washer | | A/T | 49 N•m (36 lb-ft) |
| | | | | x | | | | Fill Plug Washer | | A/T | 44 N•m (32 lb-ft) |
| | | | | x | | | | Drain Bolt Washer | | Transfer Assembly (4WD) | 44 N•m (32 lb-ft) |
| | | | | x | | | | Fill Plug Washer | | Transfer Assembly (4WD) | 44 N•m (32 lb-ft) |
| | | | | | x | | | Spark Plugs | | 1.0 – 1.1 mm (0.039 – 0.043 in)** | 22 N•m (16 lb-ft) |
| | | | | | | x | | Drain Bolt Washer | | Rear Differential (4WD) | 47 N•m (35 lb-ft) |
| | | | | | | | x | Fill Plug Washer | | Rear Differential (4WD) | 47 N•m (35 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|-------------------------|----------------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 4.5 qt. (w/ filter) |
| | | | 4.2 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 2.0 gal. |
| A/T Fluid | ATF DW-1 | 08200-9008 | 3.6 qt. (w/ cooler) |
| | | | 3.3 qt. (w/o cooler) |
| Transfer Assembly Fluid | HGO-1 | 08200-9014 | 0.5 qt. |
| Rear Differential Fluid | Honda VTM-4 Fluid | 08200-9003 | 2.8 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |
| Power Steering Fluid | Power Steering Fluid | 08206-9002 | |

*** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------|
| Front, New | Service Limit | Thickness |
| 11 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|--------------|
| 9-11 Clicks* |

* When lever is pulled with 294 N (30.0 kgf, 66.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | 6 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | | Wheel Nuts | Gray Wrench | | 127 N•m (94 lb-ft) |
| | | | x | | | | | Air Cleaner Element | | | |
| | | | x | | | | | Dust & Pollen Filter | | | |
| | | | | x | | | | Drain Bolt Washer | | A/T | 49 N•m (36 lb-ft) |
| | | | | x | | | | Fill Plug Washer | | A/T | 44 N•m (32 lb-ft) |
| | | | | x | | | | Drain Bolt Washer | | Transfer Assembly (4WD) | 44 N•m (32 lb-ft) |
| | | | | x | | | | Fill Plug Washer | | Transfer Assembly (4WD) | 44 N•m (32 lb-ft) |
| | | | | | x | | | Spark Plugs | | 1.0 – 1.1 mm (0.039 – 0.043 in)** | 22 N•m (16 lb-ft) |
| | | | | | | x | | Drain Bolt Washer | | Rear Differential (4WD) | 47 N•m (35 lb-ft) |
| | | | | | | | x | Fill Plug Washer | | Rear Differential (4WD) | 47 N•m (35 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|-------------------------|--------------------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 5.7 qt. (w/ filter) |
| | | | 5.4 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.93 gal. |
| A/T Fluid | ATF DW-1 | 08200-9008 | 3.3 qt. |
| Transfer Assembly Fluid | HGO-1 | 08200-9014 | 0.5 qt. |
| Rear Differential Fluid | Honda Dual Pump Fluid II | 08200-9007 | 1.92 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------|
| Front, New | Service Limit | Thickness |
| 11 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|--------------|
| 9-11 Clicks* |

* When lever is pulled with 294 N (30.0 kgf, 66.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | 6 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | | Wheel Nuts | Gray Wrench | | 127 N•m (94 lb-ft) |
| | | | x | | | | | Air Cleaner Element | | | |
| | | | x | | | | | Dust & Pollen Filter | | | |
| | | | | x | | | | Drain Bolt Washer | | A/T | 35 N•m (26 lb-ft) |
| | | | | x | | | | Fill Plug Washer | | A/T | 35 N•m (26 lb-ft) |
| | | | | x | | | | Drain Bolt Washer | | Transfer Assembly (4WD) | 44 N•m (32 lb-ft) |
| | | | | x | | | | Fill Plug Washer | | Transfer Assembly (4WD) | 44 N•m (32 lb-ft) |
| | | | | | x | | | Spark Plugs | | 1.0 – 1.1 mm (0.039 – 0.043 in)** | 22 N•m (16 lb-ft) |
| | | | | | | x | | Drain Bolt Washer | | Rear Differential (4WD) | 47 N•m (35 lb-ft) |
| | | | | | | | x | Fill Plug Washer | | Rear Differential (4WD) | 47 N•m (35 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|-------------------------|--------------------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 5.7 qt. (w/ filter) |
| | | | 5.4 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 2.0 gal. |
| A/T Fluid | ATF Type 3.1**** | 08200-9017 | 3.5 qt. |
| Transfer Assembly Fluid | HGO-1 | 08200-9014 | 0.5 qt. |
| Rear Differential Fluid | Honda Dual Pump Fluid II | 08200-9007 | 1.92 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.

**** Do not check the ATF fluid level unless you are replacing it.

NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | | | |
|--------------------------|---------------|-----------|---|-----|
| Front, New | Service Limit | Thickness | | |
| 11 mm | 1.6 mm | > 5 | 4 | ≤ 3 |
| Rear, New | Service Limit | Thickness | | |
| 10 mm | 1.6 mm | > 5 | 4 | ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|---------------|
| 10-12 Clicks* |

* When lever is pulled with 294 N (30.0 kgf, 66.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | 6 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | | Wheel Nuts | Gray Wrench | | 127 N•m (94 lb-ft) |
| | | | x | | | | | Air Cleaner Element | | | |
| | | | x | | | | | Dust & Pollen Filter | | | |
| | | | | x | | | | Drain Bolt Washer | | A/T | 49 N•m (36 lb-ft) |
| | | | | x | | | | Fill Plug Washer | | A/T | 44 N•m (32 lb-ft) |
| | | | | x | | | | Drain Bolt Washer | | Transfer Assembly (4WD) | 44 N•m (32 lb-ft) |
| | | | | x | | | | Fill Plug Washer | | Transfer Assembly (4WD) | 44 N•m (32 lb-ft) |
| | | | | | x | | | Spark Plugs | | 1.0 – 1.1 mm (0.039 – 0.043 in)** | 22 N•m (16 lb-ft) |
| | | | | | | x | | Drain Bolt Washer | | Rear Differential (4WD) | 47 N•m (35 lb-ft) |
| | | | | | | | x | Fill Plug Washer | | Rear Differential (4WD) | 47 N•m (35 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|-------------------------|----------------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 4.5 qt. (w/ filter) |
| | | | 4.2 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.7 gal. |
| A/T Fluid | ATF DW-1 | 08200-9008 | 3.3 qt. |
| Transfer Assembly Fluid | HGO-1 | 08200-9014 | 0.5 qt. |
| Rear Differential Fluid | Honda VTM-4 Fluid | 08200-9003 | 2.8 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |
| Power Steering Fluid | Power Steering Fluid | 08206-9002 | |

*** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------|
| Front, New | Service Limit | Thickness |
| 12 mm | 1.0 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 10 mm | 1.0 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.



1 Tire Pressure Specifications

| All | Spare Tire |
|------------------------------|---|
| See Driver's Doorjamb Label. | Spare tire pressure is 60 psi unless otherwise specified. |

2 Parking Brake Clicks

| All |
|--------------|
| 9-11 Clicks* |

* When lever is pulled with 294 N (30.0 kgf, 66.1 lbf) of force

3 Battery Information

For CCA rating, always check the label on the top of the battery. For dealer-installed battery part numbers, see the latest parts catalog

4 Parts Requirement Quick Reference

| A | B | 1 | 2 | 3 | 4 | 5 | 6 | Description | Special Tools | Remarks | Torque Specs |
|---|---|---|---|---|---|---|---|---|-------------------|-----------------------------------|--------------------|
| x | x | | | | | | | Drain Bolt Washer (replace at every oil change) | Yellow Wrench | | 40 N•m (30 lb-ft) |
| | x | | | | | | | Oil Filter | Light Blue Wrench | ¾ turn clockwise | 12 N•m (9 lb-ft) |
| | | x | | | | | | Wheel Nuts | Gray Wrench | | 127 N•m (94 lb-ft) |
| | | | x | | | | | Air Cleaner Element | | | |
| | | | x | | | | | Dust & Pollen Filter | | | |
| | | | | x | | | | Drain Bolt Washer | | A/T | 49 N•m (36 lb-ft) |
| | | | | x | | | | Fill Plug Washer | | A/T | 44 N•m (32 lb-ft) |
| | | | | x | | | | Drain Bolt Washer | | Transfer Assembly (4WD) | 44 N•m (32 lb-ft) |
| | | | | x | | | | Fill Plug Washer | | Transfer Assembly (4WD) | 44 N•m (32 lb-ft) |
| | | | | | x | | | Spark Plugs | | 1.0 – 1.1 mm (0.039 – 0.043 in)** | 22 N•m (16 lb-ft) |
| | | | | | | x | | Drain Bolt Washer | | Rear Differential (4WD) | 47 N•m (35 lb-ft) |
| | | | | | | | x | Fill Plug Washer | | Rear Differential (4WD) | 47 N•m (35 lb-ft) |

** Do not adjust the gap on iridium-tipped spark plugs.

5 Oil & Fluid Requirements

| Item | Weight / Type | Part Number | Capacity |
|-------------------------|--------------------------|-------------|----------------------|
| Engine Oil | 0W-20 | 08798-9036 | 5.7 qt. (w/ filter) |
| | | | 5.4 qt. (w/o filter) |
| Antifreeze / Coolant | Type 2*** | 0L999-9011 | 1.9 gal. |
| A/T Fluid | ATF DW-1 | 08200-9008 | 3.3 qt. |
| Transfer Assembly Fluid | HGO-1 | 08200-9014 | 0.45 qt. |
| Rear Differential Fluid | Honda Dual Pump Fluid II | 08200-9007 | 1.9 qt. |
| Brake Fluid | DOT 3 | 08798-9008 | |

*** Type 2 Antifreeze / Coolant is premixed.

NOTE: Always check the oil and fluid after filling.

6 Brake Inspection

| Brake Pad Specifications | | |
|--------------------------|---------------|-----------|
| Front, New | Service Limit | Thickness |
| 11 mm | 1.6 mm | > 5 4 ≤ 3 |
| Rear, New | Service Limit | Thickness |
| 10 mm | 1.6 mm | > 5 4 ≤ 3 |

7 Additional Parts

See the latest parts catalog.